

# OVC-4U18-PWU

## Card Cage Power Supply

### Introduction

Power supply cards are dual load-sharing and automatically switch over in the event of a power failure. A single card is sufficient to fully power the chassis. The AC power supply automatically adjusts for 90 to 264 VAC input and 47 to 63 Hz operation.

The power module OVC-4U18-PWU has passed various safety verifications and has mechanisms such as overcurrent, overvoltage and short circuit protection.

### Features

- Hot-Swappable
- Load Sharing
- Failure alarm LED indicator for local loss of power indication.
- Redundant with Automatic Failure Switchover

### Specifications

Electrical	Input Voltage	90-264VAC @130W Maximum
	Output Voltage	12VDC@10.8A
Fusing	1.25A slow blow (rack power supply) Plug-in modules individually electronically fused. Each power supply unit is individually fused.	
Power Indicator	Power/Alarm	
AC Lind Cord	Detacheable, IEC-connected. Allow easy field replacemnt or exchange for various worldwide AC power plug configurations.	
Mechanical	Size (W x H x D)	440x178x240mm
	Weight	475g
Environmental	MTBF	> 100000 hours
	Operating Temperature	-40 ° C ~75 ° C
	Storage Temperature	-40 ° C ~85 ° C
Certification Compliance		FCC/CE



More information please check on our website at [www.hoatech.com.tw](http://www.hoatech.com.tw)