



HDM-1C

1 x HDMI/CVBS to 1 x DVB-C

HOATECH TECHNOLOGIES CO., LTD.



Hoatech

A new look for our classic digital modulator HDM series.

The HDM-1C provides you with more flexible installation solutions, you can choose stand-alone, wall-mount, 1U rack mount, 1U couple mount, and 4U rack mount for installations of up to 10 modulators. The HDM-1C can convert the audio and video signal (HDMI/AV) from an external media source (DVR, satellite receiver, Blu-ray DVD player, Smart TV receiver etc.) into a DVB-C digital television channel. The channel generated from the source can be mixed together with the QAM signals. It can all be distributed over a single coaxial cable and the media contents displayed on any of the receiver devices in the installation.

This series is ideal for multi-dwelling building, clubs, restaurants, hospital, motels and Hotels

FEATURES

- **HDMI/AV input**
- **HDMI 1.3**
- **HDCP 1.4**
- **ETS 300 429 DVB-C standard**
- **High-quality encoding**
- **Automatic detection of the input resolution**
- **Programmable parameters**
- **Wall or rack mount options**
- **User friendly interface**
- **Supports flexible installation solutions**



1U rack mount



Couple mount



4U rack mount

**100%
TAIWAN
MANUFACTURED**





SPECIFICATIONS

INPUT

Video & Audio input | 1x HDMI/CVBS

Connector Type | HDMI Type A receptacle/RCA

Input Video Resolution | Up to 1080p@60Hz

Output Video Resolution | Up to 1080p@30Hz

PC Resolution | 800×600 / 1024×768/1280×600
1280×720 / 1280×768 / 1360×768/1366×768

Audio | HDMI/RCA (Left, Right stereo channels)

DVB-C OUTPUT

DVB-C Standard | DVB-C (ETS 300 429)

Symbol Rate | Up to 6.96 M Symbol/S

Constellation | 16/32/64/128/256QAM

RF Carrier | 1

Frequency | 100-860 MHz

Output level | 85-105 dBμV

MER | > 42 dB

Connector Type | 'F' female connector

SYSTEM

Video encoding | H.264/AVC

Audio encoding | MPEG-1 audio layer II

Audio bit rate | 192 Kbps

PID Setting | PMT/ Video & Audio/ PCR

PSI | NID/ ONID/P.D.S./TS ID

LCN | Up to 1023

Service Name | At most 15 characters

CONFIGURATION

On-site management | LCD panel & Buttons

GENERAL

Type | Stand-alone

Dimensions/Weight | 146x195x40mm/0.88kg

Power supply | DC 12V/1A external power supply

Power consumption | 8W

Operation temperature | 0 to +55 °C

Accessories | DC 12V/1A external power supply

Hoatech Technologies Co., Ltd.

2F, No.15, Xingfu St. Zhubei City, Hsinchu County 30271, Taiwan (R.O.C)

Phone: +886-3-6576647 **Fax:**+886-3-6576797

www.hoatech.com.tw **E-mail:**sales@hoatech.com.tw

Publish Date: 2020/11/3 V1.2

© Copyright 2020 Hoatech Technologies Co., Ltd. and the Hoatech logo are trademarks of Hoatech Technologies Co., Ltd. All rights reserved. All other trademarks are the property of their respective owners.